



MEMBER  
THE INDIAN PAINT ASSOCIATION



# Jai Kamal Paints

MANUFACTURERS OF PAINTS & VARNISH

## EPIJAY

### EOPXY PUTTY

<b>DESCRIPTION</b>	:	<i>'Epijay'</i> Epoxy Putty is a two pack filler paste compound formulated for filling undulations, pits and dents on primed metal substrate or concrete surface. Offers high degree of radiation resistance.
<b>TYPE</b>	:	Two Pack
<b>CONSISTENCY</b>	:	Thick, Uniform Paste
<b>FINISH</b>	:	Matt
<b>COLOUR</b>	:	Grey
<b>FLASH POINT</b>	:	Above 20 °C
<b>MIXING RATIO</b>	:	Base: Accelerator; 9 : 1
<b>POT LIFE</b>	:	2 - 4 hr. It is advisable to mix only small quantity at a time and use within 1 hr. pot life depends on ambient temp. & quantity of paste mixed at a time.
<b>DRYING TIME</b>	:	Surface Dry – 2 to 3 hrs. Hard Dry – 18 hrs.
<b>METHOD OF APPLICATION</b>	:	Knife or Putty Blade.
<b>TYPICAL FILM THICKNESS</b>	:	250 – 375 Microns
<b>COVERAGE</b>	:	1.4 – 0.9
<b>INTERVAL BEFORE WET CUTTING</b>	:	24 hrs. minimum

'THE DECORATIVE PROTECTION THAT STANDS THE TEST OF TIME'

(Old No.70) New No 169 MS KOIL STREET, ROYAPURAM, CHENNAI-600 013, Ph 2598 1323 2595 6660



MEMBER  
THE INDIAN PAINT ASSOCIATION



# Jai Kamal Paints

**MANUFACTURERS OF PAINTS & VARNISH**

<b>INTERVAL BEFORE OVER COATING</b>	:	Minimum – 24 hrs. Maximum – 7 Days
<b>STORAGE LIFE</b>	:	9 months
<b>SURFACE PREPARATION</b>	:	The surface should be cleaned, and well primed.
<b>THINNER</b>	:	'Epijay' Epoxy Thinner

(THE INFORMATION IN THIS LEAFLET IS GIVEN IN GOOD FAITH, BUT WITHOUT WARRANTY)

# Jai Kamal Paints

**'THE DECORATIVE PROTECTION THAT STANDS THE TEST OF TIME'**

(Old No.70) New No 169 MS KOIL STREET, ROYAPURAM, CHENNAI-600 013, Ph 2598 1323 2595 6660