



MEMBER
THE INDIAN PAINT ASSOCIATION



Jai Kamal Paints

MANUFACTURERS OF PAINTS & VARNISH

FERROTEX

CHIMNEY BLACK

| | | |
|-------------------------------------|---|---|
| DESCRIPTION | : | A specially formulated bituminous coating for application on metal surface exposed to high temperature. It protects the surface from atmospheric corrosion, chemical fumes and industrial gases. It has excellent weatherability good flexibility and abrasion resistance |
| TYPE | : | Single Pack; Air Drying |
| COMPOSITION | : | Bituminous medium suitably pigmented. |
| COLOUR | : | Black |
| APPLICATION | : | Brush |
| THEORETICAL COVERAGE | : | 14 Sqmt. per ltrs. |
| RECOMMENDED DFT | : | 40 Microns per coat |
| DRYING TIME | : | Touch Dry – 4 hrs. |
| OVERCOATING INTERVAL | : | 24 hrs. |
| FLASH POINT | : | Above 30 °C |
| THINNER | : | 'Jai' Thinner |
| FINISH | : | Semi Glossy |
| TEMPERATURE RESISTANCE | : | 250 °C Dry Heat |
| STORAGE | : | Upto 12 months. Materials to be kept in original sealed container in dry place under normal temperature conditions. |
| NOTES ON SURFACE PREPARATION | : | Make full use of mechanical tools along with manual chipping and wire brushing to remove loose rust and scale st.2. The surface should be clean and dry before application. |

'THE DECORATIVE PROTECTION THAT STANDS THE TEST OF TIME'

(Old No.70) New No 169 MS KOIL STREET, ROYAPURAM, CHENNAI-600 013, Ph 2598 1323 2595 6660



MEMBER
THE INDIAN PAINT ASSOCIATION



Jai Kamal Paints

MANUFACTURERS OF PAINTS & VARNISH

METHOD OF APPLICATION : Stir the contents thoroughly before and during use.
Apply by brush directly on the surface.
Application to be carried out on cold surface only.

AERAS OF APPLICATION : Exterior surface of chimney, stack, furnace etc.

(THE INFORMATION IN THIS LEAFLET IS GIVEN IN GOOD FAITH, BUT WITHOUT WARRANTY)

Jai Kamal Paints

'THE DECORATIVE PROTECTION THAT STANDS THE TEST OF TIME'

(Old No.70) New No 169 MS KOIL STREET, ROYAPURAM, CHENNAI-600 013, Ph 2598 1323 2595 6660