# Jai Kamal Paints

#### MANUFACTURERS OF PAINTS & VARNISH

### **FERROTEX**

### **HEAT RESISTING ALUMINIUM PAINT 200°C**

**DESCRIPTION**: A two pack high lustre Aluminium Paint with remarkable

protection properties and temperature resistance upto 250 °C. The product is ideally suited for turbines, boilers, chimney, furnaces and equipments required to withstand dry heat. It also shows excellent performance in both interior and exterior application in buildings, offices, factories, industrial plants were house etc and has special use in coating exterior of storage tanks in oil industries because of its heat

reflectant property.

Minimum: 24 hrs.

TYPE : Two Pack

**COMPOSITION**: Oleoresinous medium with leafing aluminium.

COLOUR : Aluminium

**APPLICATION**: Brush / Conventional Spray

**THEORETICAL**: 18 - 20 Sqmt. / ltr.

COVERAGE

**RECOMMENDED DFT**: 15 - 20 Microns per coat

**DRYING TIME** : Touch Dry 4 hrs.

INTERVAL

**OVERCOATING** 

**FLASH POINT** : Above 30 °C

**THINNER**: 'JAI' Thinner

**TEMPERATURE** : 250 °C Dry Heat

**RESISTANCE** 



# Jai Kamal Paints

#### MANUFACTURERS OF PAINTS & VARNISH

**STORAGE** Upto 12 months. Materials to be kept in original sealed

container in dry place under normal temperature condition.

**RECOMMENDED** 

**PRIMER** 

'Jaytex' Inorganic Zinc Primer.

**FINISH Bright Metallic** 

**NOTE ON SURFACE** 

**PREPARATION** 

Make full use of mechanical tools along with manual chipping and wire brushing to remove loose rust and scale to SA 2½.

**METHOD OF** 

**APPLICATION** 

Mix the paste into the medium and stir the contents thoroughly

before and occasionally during use.

Application by conventional spray; brush

LIMITATION No recommended for acidic areas.

SINE

(THE INFORMATION IN THIS LEAFLET IS GIVEN IN GOOD FAITH, BUT WITHOUT WARRANTY)

