



MEMBER
THE INDIAN PAINT ASSOCIATION



Jai Kamal Paints

MANUFACTURERS OF PAINTS & VARNISH

JAI

PRIMER SURFACER

DESCRIPTION	:	'Jai' Primer – Surfacer works as a good corrosion - resistant primer an filler. As a filler it can be used to cover minor surface imperfections. It has good adhesion when used directly on bare metals. It has excellent adhesion on primed surfaces.
AREAS OF APPLICATION	:	Ferrous and non-ferrous metals, wood, etc.
VISCOSITY OF SUPPLY:	:	45 – 55 Secs, by Ford Cup B4 at 30 °C
THINNER RECOMMENDED	:	G.P Thinner
METHOD OF APPLICATION	:	Spray, Brush
APPLICATION VISCOSITY	:	Brushing – 45 to 50 Secs. Spraying – 20 to 25 Secs. At a pressure of 40 – 50 p.s.i.
DRYING TIME	:	Surface Dry – Less than 30 minutes Hard Dry – Less than 8 hrs.
FINISH	:	Smooth and Matt
COVERING CAPACITY	:	14 – 16 Sqmt. / ltr per coat by brushing
FLASH POINT	:	Above 95 °F (35 °C)
SHADE AVAILABLE	:	Grey and White

'THE DECORATIVE PROTECTION THAT STANDS THE TEST OF TIME'

(Old No.70) New No 169 MS KOIL STREET, ROYAPURAM, CHENNAI-600 013, Ph 2598 1323 2595 6660



MEMBER
THE INDIAN PAINT ASSOCIATION



Jai Kamal Paints

MANUFACTURERS OF PAINTS & VARNISH

DIRECTIONS FOR USE:

Degrease and derust the surface by suitable treatment. Ensure that the surface is free from moisture and loose matter. Apply '*Jai*' Primer Surfacer and Brushing filler either by brushing or spraying. Use the recommended thinner for bringing down the consistency to the recommended level.

After drying of the primer surfacer and prior to the application of other coats, dry-sand the surface using 220 or 280 grade emery paper.

(THE INFORMATION IN THIS LEAFLET IS GIVEN IN GOOD FAITH, BUT WITHOUT WARRANTY)

Jai Kamal Paints

'THE DECORATIVE PROTECTION THAT STANDS THE TEST OF TIME'

(Old No.70) New No 169 MS KOIL STREET, ROYAPURAM, CHENNAI-600 013, Ph 2598 1323 2595 6660