



MEMBER  
THE INDIAN PAINT ASSOCIATION



# Jai Kamal Paints

MANUFACTURERS OF PAINTS & VARNISH

## JAI KAMAL

### HB POLYURETHANE FINISH

DESCRIPTION	:	A high build Polyurethane Finish – it offers outstanding resistance to a wide range of corrosive conditions. Provides a hard, tough, flexible and abrasion resistant coating and has excellent resistance to acid, alkali, solvent, water and salt solutions when applied over suitable primer.
COLOUR	:	Assorted Shades
TYPE	:	Two Pack; Cold Cured
COMPOSITION	:	Acrylic – Aliphatic Polyisocyanate with weather resistant pigments.
MIXING RATIO	:	Base: Accelerator; 4 : 1 by volume
POT LIFE	:	4 – 6 hrs.
FINISH	:	Semi Glossy
FLASH POINT	:	Above 20 °C
TEMPERATURE RESISTANCE	:	120 °C Dry Heat
RECOMMENDED DFT	:	50 – 60 Microns
THEORETICAL COVERING	:	10 Sqmt. per ltr.
DRYING TIME	:	Touch Dry – 3 hr.
OVERCOATING INTERVAL	:	Minimum 16 hrs. Maximum 7 days
METHOD OF APPLICATION	:	Airless / Conventional Spray; Brush

‘THE DECORATIVE PROTECTION THAT STANDS THE TEST OF TIME’

(Old No.70) New No 169 MS KOIL STREET, ROYAPURAM, CHENNAI-600 013, Ph 2598 1323 2595 6660



MEMBER  
THE INDIAN PAINT ASSOCIATION



# Jai Kamal Paints

**MANUFACTURERS OF PAINTS & VARNISH**

---

<b>THINNER</b>	:	<i>'Jai Kamal Pu'</i> Thinner
<b>STORAGE LIFE</b>	:	Upto 9 months. Store in cool, dry condition in original sealed packing.
<b>SURFACE PREPARATION</b>	:	Blast clean to SA 2½ grade minimum. If blast cleaning is not practical employ mechanical tools along with manual chipping and wire brushing and ensure surface is free from dust / particles.

(THE INFORMATION IN THIS LEAFLET IS GIVEN IN GOOD FAITH, BUT WITHOUT WARRANTY)

Jai Kamal Paints

---

**'THE DECORATIVE PROTECTION THAT STANDS THE TEST OF TIME'**

(Old No.70) New No 169 MS KOIL STREET, ROYAPURAM, CHENNAI-600 013, Ph 2598 1323 2595 6660