



MEMBER
THE INDIAN PAINT ASSOCIATION



Jai Kamal Paints

MANUFACTURERS OF PAINTS & VARNISH

JAI KAMAL

POLYURETHANE PAINT

DESCRIPTION : A two pack Acrylic Polyurethane Finish, based on aliphatic isocyanate adduct. It has excellent gloss & colour retention property and is resistant to humid, saline & chemical atmosphere. Suitable for application in oil refineries, steel structures, chemical plant, off-shore & marine installations power plant, pulp & paper mills, sugar industry & transportation industry.

It can be used in a total polyurethane system or as finish coat over an epoxy base coat.

MIXING RATIO : Base & Accelerator; 4:1 by volume

COLOUR : Available in all colours

FINISH : Glossy

FLASH POINT : Above 20 °C

RECOMMENDED DRY FILM THICKNESS : 30 – 40 Microns

THEORETICAL COVERING CAPACITY : 11 – 15 Sqmt. / ltr. per coat

COVERAGE WITH 20% LOSS FACTOR : 9 – 12 Sqmt. / ltr. per coat

DRYING TIME WET CUTTING : Surface Dry – in 1 hr.
Hard Dry – in 8 – 12 hrs.

CURING TIME : 7 Days

POT LIFE : 2 - 4 hrs. depending on ambient condition

INTERVAL BEFORE : Minimum – 12 hrs.

‘THE DECORATIVE PROTECTION THAT STANDS THE TEST OF TIME’

(Old No.70) New No 169 MS KOIL STREET, ROYAPURAM, CHENNAI-600 013, Ph 2598 1323 2595 6660



MEMBER
THE INDIAN PAINT ASSOCIATION



Jai Kamal Paints

MANUFACTURERS OF PAINTS & VARNISH

OVERCOATING

Maximum – 7 Days

METHOD OF APPLICATION

: Spray

THINNER

: '*Jai Kamal Polyurethane*' Thinner

STORAGE LIFE

: 6 months store in cool & dry place.

PRECAUTION WHILE PAINTING

: Avoid inhalation & contact with eye and skin.

(THE INFORMATION IN THIS LEAFLET IS GIVEN IN GOOD FAITH, BUT WITHOUT WARRANTY)

Jai Kamal Paints

'THE DECORATIVE PROTECTION THAT STANDS THE TEST OF TIME'

(Old No.70) New No 169 MS KOIL STREET, ROYAPURAM, CHENNAI-600 013, Ph 2598 1323 2595 6660