### Jai Kamal Paints

#### MANUFACTURERS OF PAINTS & VARNISH

### JAYTEX

**ALUMINIUM PAINT (IS: 2339)** 

**DESCRIPTION** 

Brilliant luster, excellent durability and corrosion resistance are the chief properties of Jaytex Aluminium Paint. It is supplied in a two pack system where the paste and medium are packed separately. Jaytex Aluminium Paint has very good hardness, flexibility and adhesion. Water resistance is also satisfactory.

Jaytex Aluminium Paint is suitable for surfaces susceptible to atmospheric corrosion and in environments where good durability is required. Good heat-resisting properties and high covering capacity coupled with long life makes this paint the most desired coating from the paint of view of economy and performance.

This paint is widely used for steel structures such as railway wagons, bridges, electrical transmission towers, oil tanks, gates and fences.

**AREAS OF** 

**APPLICATION** 

Steel structures, wagons, oil tanks etc

**VISCOSITY OF SUPPLY:** 

15 to 20 Seconds by ford cup B4 at 30° C

**THINNER** 

RECOMMENDED

Thinner 101

METHOD OF

APPLICATION

**Brushing or Spraying** 

APPLICATION VISCOSITY

15 – 20 Seconds by ford cup B4 at 30° C for brushing &

spraying.

**PRIMER** : Redoxide Primer / or 1<sup>st</sup> coat of Aluminium Paint act as primer.



## Jai Kamal Paints

#### MANUFACTURERS OF PAINTS & VARNISH

**RECOMMENDED** 

**DRYING TIME** : Surface Dry : Less than 3½ hours

Hard Dry : Overnight

FINISH : Lustrous

**COVERING CAPACITY:** 12 to 13 Sq. Meters per Litre per coat

**FLASH POINT** : Above 95° F (35° C)

**DIRECTIONS FOR USE:** Surface should be free dirt, dust, grease, rust, moisture etc. Mix

the entire quantity of supplied aluminium paste thoroughly with a small quantity of medium and then add the mixture to the remaining medium. Stir well before use it is supplied at

brushing consistency.

(THE INFORMATION IN THIS LEAFLET IS GIVEN IN GOOD FAITH, BUT WITHOUT WARRANTY)

# Jai Kamal Paints