



MEMBER
THE INDIAN PAINT ASSOCIATION



Jai Kamal Paints

MANUFACTURERS OF PAINTS & VARNISH

JAYTEX

ANTICORROSIVE REDOXIDE PRIMER

DESCRIPTION	:	A hard quick drying anticorrosive Redoxide Primer pigmented with Redoxide. It is suitable for steel surfaces in both heavy industrial and primeratmosp.
TYPE	:	Single Pack
COMPOSITION	:	Alkyd medium suitably pigmented with good Rust preventing Properties.
COLOUR	:	Redoxide
APPLICATION	:	Brush / Roller & Spray
COVERAGE	:	Theoretical – 10 Sqmt. / ltr practical – 8 Sqmt. / ltr.
DRY FILM THICKNESS	:	35 Microns / coat
DRYING TIME	:	Surface Dry – 1 ltr. Hard Dry – 8 ltrs.
SPECIFIC GRAVITY	:	1.2 – 1.4 Kg. / ltr.
VISOCITY	:	80 – 90 sec @ 35 °C
SOLIDS	:	65% by weight 57% by volume
FINISH	:	Matt
THINNER	:	Thinner – 10 – 15%
SHELF LIFE	:	12 months
FLASH POINT	:	36 °C
SURFACE PREPARATION	:	The surface should be blast cleaned / shop primed steel.
PRECAUTIONS	:	When applying this product, a mask must be worn and all contact with an open flame or open spark areas must be avoided.

(THE INFORMATION IN THIS LEAFLET IS GIVEN IN GOOD FAITH, BUT WITHOUT WARRANTY)

‘THE DECORATIVE PROTECTION THAT STANDS THE TEST OF TIME’

(Old No.70) New No 169 MS KOIL STREET, ROYAPURAM, CHENNAI-600 013, Ph 2598 1323 2595 6660