



MEMBER
THE INDIAN PAINT ASSOCIATION



Jai Kamal Paints

MANUFACTURERS OF PAINTS & VARNISH

JAYTEX

BITUMINOUS ALUMINIUM PAINT

DESCRIPTION	:	An economical two pack anticorrosive bituminous paint designed to offer high resistance to moisture, saline water and general corrosive conditions. It is excellent for protection of underground and underwater installations, structural steel exposed to corrosive industrial or coastal environments and to unexposed parts of structures, machines, railway coaches etc. which are prone to corrosion.
TYPE	:	Two Pack; Air Drying
COMPOSITION	:	Aluminium paint based on bituminous medium.
COLOUR	:	Aluminium
APPLICATION	:	Brush / Airless Spray
THEORETICAL COVERAGE	:	12 Sqmt. per ltrs.
RECOMMENDED DFT	:	30 Microns per coat
DRYING TIME	:	Touch Dry – 6 hrs.
OVERCOATING INTERVAL	:	24 hrs.
FLASH POINT	:	Above 30 °C
THINNER	:	'Jai' Thinner
FINISH	:	Metallic
TEMPERATURE RESISTANCE	:	93 °C Dry Heat
STORAGE	:	Upto 12 months. Materials to be kept in original sealed container in dry place under normal temperature conditions.

'THE DECORATIVE PROTECTION THAT STANDS THE TEST OF TIME'

(Old No.70) New No 169 MS KOIL STREET, ROYAPURAM, CHENNAI-600 013, Ph 2598 1323 2595 6660



MEMBER
THE INDIAN PAINT ASSOCIATION



Jai Kamal Paints

MANUFACTURERS OF PAINTS & VARNISH

- RECOMMENDED PRIMERS** : Jaytex antisaline metallic primer high build zinc phosphate primer.
- NOTES ON SURFACE PREPARATION** : Blast clean to a minimum of SA 2½ grade. If blasting is not practical employ mechanical tools along with manual chipping and wire brushing and ensure surface is free from dust / particles.
- METHOD OF APPLICATION** : Stir the medium and mix the paste into it. Stir the mixture thoroughly before and during use. Application by brush / airless spray.
- LIMITATION** : Does not have resistance to solvents.

(THE INFORMATION IN THIS LEAFLET IS GIVEN IN GOOD FAITH, BUT WITHOUT WARRANTY)

Jai Kamal Paints

‘THE DECORATIVE PROTECTION THAT STANDS THE TEST OF TIME’

(Old No.70) New No 169 MS KOIL STREET, ROYAPURAM, CHENNAI-600 013, Ph 2598 1323 2595 6660