

Jai Kamal Paints

MANUFACTURERS OF PAINTS & VARNISH

JAYTEX

BITUMINOUS ANTICORROSIVE BLACK PAINT

DESCRIPTION: A specially treated versatile bituminous anticorrosive

composition designed to protect ferrous surfaces which are not regularly maintained due to inaccessibility. It also resists mild acid and alkali and excellent water resistance characteristics. Serves as an economical coating for protection of undercarriage of automobiles, encased steel works, inside lining of sewage tanks, embedded wood and

concrete piles.

TYPE: Single Pack; Air Drying

COMPOSITION : Reinforced bituminous tar medium based paint.

COLOUR : Black

APPLICATION: By Brush / Roller / Airless Spray

THEORETICAL: 18 Sqmt. per ltrs.

COVERAGE

RECOMMENDED DFT: 30 Microns per coat

DRYING TIME : Touch Dry – 6 hrs.

OVERCOATING: 24 hrs.

INTERVAL

FLASH POINT : Above 23 °C

THINNER : 'Jai' Thinner

FINISH : Semi Glossy

STORAGE: Upto 12 months. Materials to be kept in original sealed container in dry place under normal temperature condition.



Jai Kamal Paints

MANUFACTURERS OF PAINTS & VARNISH

NOTES ON SURFACE:

PREPARATION

Blast clean to a minimum of SA 2½ grade. If blasting is not possible, employ mechanical tools ensure surface is free

from dust / particles.

AREAS OF APPLICATION

Undercarriage of automobiles, ice factories, sugar mills, pipelines

marine installations.

(THE INFORMATION IN THIS LEAFLET IS GIVEN IN GOOD FAITH, BUT WITHOUT WARRANTY)



SINE