



Jai Kamal Paints

MANUFACTURERS OF PAINTS & VARNISH

JAYTEX

BLACK PAINT FOR WATER TANK

DESCRIPTION	:	Air drying bitumen based paint suited for coating interior surface of mild steel tanks to hold cold fresh water (domestic, boiler feed, process and drinking water). Painting scheme consists of aluminium as primer coat and Jaytex black paint as finish coat. Provides excellent protection against corrosion and ensures that water is clear and free from bad taste and odour and is perfectly drinkable.
RECOMMENDED USE	:	In interior of tanks for domestic, drinking and industrial Water.
SURFACE PREPARATION	:	Degrease and clean – blast / Manual / Mechanical method. Allow surface to dry before painting.
METHOD OF PREPARATION	:	Brush / Roller / Spray Airless Spray recommended for uniform and high film build
FINISH	:	Aluminium – Semigloss Black – Glossy
FLSAH POINT	:	Above 30 °C
RECOMMENDED DRY FILM THICKNESS PER COAT	:	Aluminium – 50 Microns Black – 25 Microns
CORRESPONDING WET: FILE THICKNESS	:	Aluminium – 111 Microns. Black – 71 Microns
COVERING CAPACITY	:	Aluminium – 9 Sqmt. per ltrs. Black – 14 Sqmt. per ltrs.

‘THE DECORATIVE PROTECTION THAT STANDS THE TEST OF TIME’

(Old No.70) New No 169 MS KOIL STREET, ROYAPURAM, CHENNAI-600 013, Ph 2598 1323 2595 6660



MEMBER
THE INDIAN PAINT ASSOCIATION



Jai Kamal Paints

MANUFACTURERS OF PAINTS & VARNISH

DRYING TIME	:	Surface Dry : 4 hrs. Hard Dry : 8 – 12 hrs. Full Curing : 7 – 10 Days
INTERVAL BEFORE OVER COATING	:	Minimum 24 hrs.
THINNER	:	'Jaytex' Thinner
STORAGE	:	9 months
PRECAUTIONS	:	Efficient ventilation should be provided while painting. Before tanks are put to use flush out with clean fresh water 2 – 3 times.
COLOUR AVAILABLE	:	Aluminium – Silver Black - Black

(THE INFORMATION IN THIS LEAFLET IS GIVEN IN GOOD FAITH, BUT WITHOUT WARRANTY)

Jai Kamal Paints

'THE DECORATIVE PROTECTION THAT STANDS THE TEST OF TIME'

(Old No.70) New No 169 MS KOIL STREET, ROYAPURAM, CHENNAI-600 013, Ph 2598 1323 2595 6660