



MEMBER
THE INDIAN PAINT ASSOCIATION



Jai Kamal Paints

MANUFACTURERS OF PAINTS & VARNISH

JAYTEX

HEAT RESISTING SILICONE ALUMINIUM PAINT

- DESCRIPTION** : Two / single pack Aluminium finish coat for heat resistance at high temperature used for coating exhaust systems, exterior of chimney, stacks ovens, kilns etc. exposed to dry heat temperature ranging from 400 °C to 600 °C.
- COLOUR** : Aluminium
- FINISH** : Bright and Metallic
- COMPOSITION** : Silicone resin with leafing aluminium paste.
- APPLICATION** : Brush / Roller
- DRYING TIME** : Touch Dry 3 - 4 hrs.
- OVERCOATING INTERVAL** : 24 hrs.
- FLASH POINT** : Above 25 °C
- FILM THICKNESS** : 15 – 20 Microns
- COVERING CAPACITY** : 8 – 10 Sqmt / ltr.
- RECOMMENDED THINNER** : 'Jaytex' Stoving Thinner.
- SHELF LIFE** : 6 months in sealed containers. Keep in dry place.
- NOTE ON SURFACE PREPARATION** : Degrease and blast clean to SA 2½ grade minimum. If blast cleaning is not possible use mechanical or manual means to get an absolutely clean metal surface free from rust and all other contaminations. Wipe with clean rag soaked with paint thinners.
- PRECAUTIONS** : Not to be used in areas of high acidity or alkalinity. Does not cure and remains soft until temperature reaches 200 °C. At the time of application, metal must be at room temperature. Avoid applying thick coat since that may cause blistering.

(THE INFORMATION IN THIS LEAFLET IS GIVEN IN GOOD FAITH, BUT WITHOUT WARRANTY)

'THE DECORATIVE PROTECTION THAT STANDS THE TEST OF TIME'

(Old No.70) New No 169 MS KOIL STREET, ROYAPURAM, CHENNAI-600 013, Ph 2598 1323 2595 6660