



MEMBER
THE INDIAN PAINT ASSOCIATION



Jai Kamal Paints

MANUFACTURERS OF PAINTS & VARNISH

JAYTEX

HIGH BUILD BLACK

DESCRIPTION	:	A high build economical phenolic bitumen based anticorrosive paint designed to protect steel surfaces from corrosion, cement surfaces from erosion and as water proof coating to protect wood, steel, asbestos, cement and concrete surfaces. It is resistant to mild acids, alkali and chemicals. It affords excellent abrasion resistance and weatherability
TYPE	:	Single Pack; Air Drying
COMPOSITION	:	Phenolic bitumen medium suitably pigmented.
COLOUR	:	Black / Brown
APPLICATION	:	By Brush / Roller / Airless Spray
THEORETICAL COVERAGE	:	7.5 Sqmt. per ltrs.
RECOMMENDED DFT	:	100 Microns per coat
DRYING TIME	:	Touch Dry – 6 hrs.
OVERCOATING INTERVAL	:	24 hrs.
FLASH POINT	:	Above 25 °C
THINNER	:	'Jai' Thinner
FINISH	:	Semi Glossy
TEMPERATURE RESISTANCE	:	80 °C Dry Heat
STORAGE	:	Upto 12 months. Materials to be kept in original sealed container in dry place under normal temperature conditions.

'THE DECORATIVE PROTECTION THAT STANDS THE TEST OF TIME'

(Old No.70) New No 169 MS KOIL STREET, ROYAPURAM, CHENNAI-600 013, Ph 2598 1323 2595 6660



MEMBER
THE INDIAN PAINT ASSOCIATION



Jai Kamal Paints

MANUFACTURERS OF PAINTS & VARNISH

RECOMMENDED PRIMERS : Jaytex antisaline metallic primer high build zinc phosphate primer, zinc chromate primer.

NOTES ON SURFACE PREPARATION : Degrease and blast clean to SA 2½ grade minimum. If blast cleaning is not practical, then mechanical cleaning by use of tools along with manual chipping and wire brushing should be done. The surface should be clean and dry.

Concrete: New surface should have been cured for a minimum of 3 months. Surface should be made rough and free from contaminants by sand sweeping.

For old surface, remove all salt deposits by water jet washing. Ensure all dust / particles are fully removed by suction or air blast and surface is clean and dry.

METHOD OF APPLICATION : Stir the contents thoroughly before and during use. Application by brush / roller / airless spray.

AERAS OF APPLICATION : Barrage gates, coal bunkers, jetties, marine installations, penstocks, pipelines, structures inside chemical factories, underframes of railway coaches and lorries etc.

(THE INFORMATION IN THIS LEAFLET IS GIVEN IN GOOD FAITH, BUT WITHOUT WARRANTY)

Jai Kamal Paints

'THE DECORATIVE PROTECTION THAT STANDS THE TEST OF TIME'

(Old No.70) New No 169 MS KOIL STREET, ROYAPURAM, CHENNAI-600 013, Ph 2598 1323 2595 6660