Jai Kamal Paints

MANUFACTURERS OF PAINTS & VARNISH

JAYTEX

HIGH BUILD ZINC PHOSPHATE PRIMER

DESCRIPTION: A high build, hard drying anticorrosive primer for steel based

on synthetic resin medium and zinc phosphate pigment. Recommended for external and internal surfaces subjected to humidity, condensation, marine and coastal environments. It is compatible with a wide range of top coats like synthetic enamel, bituminous paints, aluminium paints, chlorinated

rubber based paints etc.

TYPE : Single Pack; Air Drying

COLOUR : Grey

FINISH : Matt to Egg Shell

COMPOSITION : Modified alkyd medium pigmented with zinc phosphate.

% OF SOLIDS VOLUME: 46 + 2%

TEMPERATURE : 100 °C Dry Heat

RESISTANCE

APPLICATION: Brush or Spray

DRY FILM THICKNESS: 35 - 50 Microns per Coat

COVERAGE : 13.5 Sqmt. at 35 Microns DFT

9.4 Sqmt. at 50 Microns DFT

DRYING TIME : Touch Dry : 1 - 2 hrs.

Hard Dry: 10 - 12 hrs.

OVERCOATING

INTERVAL

Minimum 18 hrs.

FLASH POINT : Above 30 °C

THINNER : 'Jai' Thinner



Jai Kamal Paints

MANUFACTURERS OF PAINTS & VARNISH

STORAGE LIFE : 12 months in original sealed container stored under normal

temperature condition.

SURFACE : Degrease & blast clean to SA 2½ grade, or manual cleaning

by chipping, scraping, wire brushing to remove all dust, scales,

loose particles, contamination etc.

LIMITATIONS : Not to be used for continuous immersions in water.

USE : General structural steel, mining & machinery industries, petro

chemical installations, pipe lines, tank form, and ship structures.

(THE INFORMATION IN THIS LEAFLET IS GIVEN IN GOOD FAITH, BUT WITHOUT WARRANTY)

Jai Kamal Paints

SINE