

# Jai Kamal Paints

### MANUFACTURERS OF PAINTS & VARNISH

## **JAYTEX**

## **RED LEAD PRIMER (IS 102)**

**DESCRIPTION**: 'Jaytex' Red lead primer designed for excellent rust inhibitive

properties with linseed oil medium exclusively pigmented with red lead conforming to IS 102. It can be overcoated with aluminium paint or synthetic enamel paint. Specially suited for surface where hard and tightly bound millscale cannot be removed easily. Suitable for application on steel structures

exposed to marine atmosphere.

**TYPE**: Single Pack, Air Drying

**COMPOSITION** : Linseed oil medium exclusively pigmented with red lead

conforming to IS 102.

**COLOUR** : Orange

**APPLICATION**: Brush/ Roller

THEORETICAL : 20Sqmt./ltr

**COVERAGE** 

**RECOMMENDED DFT**: 35-40 Microns per coat

**OVERCOATING**: Mnimum 48 hrs.

**INTERVAL** 

**FLASH POINT**: Above 30 C

THINNER : 'Jai' G.P Thinner

FINISH : Semi glossy

**TEMPERATURE** : 120 C Dry Heat

RESISTANCE

STORAGE: Upto 6 months. Material to be kept in original sealed container

in dry place under normal temperature condition.



# Jai Kamal Paints

#### MANUFACTURERS OF PAINTS & VARNISH

**OVERCOATS** Aluminium paint; synthetic enamel paint.

SINE

**SURFACE** Sand blasting to SA 21/2 grade. If sand blasting is not **PREPARATION** 

practicable employ mechanical cleaning and ensure surface is

free from dust and contaminants.

**METHOD OF** 

**APPLICATION** 

Stir the content thoroughly before and during use. Application

by brush or roller.

**AREA OF** 

**APPLICATION** 

Suitable for steel works exposed to marine atmosphere.

(THE INFORMATION IN THIS LEAFLET IS GIVEN IN GOOD FAITH, BUT WITHOUT WARRANTY)