



MEMBER
THE INDIAN PAINT ASSOCIATION



Jai Kamal Paints

MANUFACTURERS OF PAINTS & VARNISH

JAYTEX MARINE ENAMEL

DESCRIPTION	:	A Hard drying silky alkyd paint for use on super structures and on steel surfaces has good resistance to sea environment. It is used as the medium or final layer, when painting metal surfaces on ships that are above top shipping line
TYPE	:	Single pack
COMPOSITION	:	Alkyd medium suitably pigmented.
COLOUR	:	Standard Shades
APPLICATION	:	Brush / Roller & Spray
COVERING	:	Theoretical – 12 Sqmt. / ltrs. Practical – 10 Sqmt. / ltrs.
DRY FILM THICKNESS	:	35 – 40 Microns / Coat.
DRYING TIME	:	Surface Dry – 3 hrs. Hard Dry – 5-6 hrs.
SPECIFIC GRAVITY	:	1.05 – 1.2 Kg / ltrs.
VISCOCITY	:	70 – 80 Sec @ 35 °C
SOLIDS	:	55% by Weight 45% by Volume
FINISH	:	Smooth
THINNER	:	Marine Thinner
SHEET LIFE	:	12 Months

‘THE DECORATIVE PROTECTION THAT STANDS THE TEST OF TIME’

(Old No.70) New No 169 MS KOIL STREET, ROYAPURAM, CHENNAI-600 013, Ph 2598 1323 2595 6660



MEMBER
THE INDIAN PAINT ASSOCIATION



Jai Kamal Paints

MANUFACTURERS OF PAINTS & VARNISH

SURFACE PROPARATION

: The surface should be clean of rust, oily substances, as well as fragments of old paints, corrosion spots, humidity and seasalt. The surface is primed with Jaytex Marine Redoxide Primer and then Jaytex marine finish is applied.

PRECAUTIONS

: When applying this product, a mask must be worn and all contact with an open flame or open spark areas must be avoided.

(THE INFORMATION IN THIS LEAFLET IS GIVEN IN GOOD FAITH, BUT WITHOUT WARRANTY)

Jai Kamal Paints

'THE DECORATIVE PROTECTION THAT STANDS THE TEST OF TIME'

(Old No.70) New No 169 MS KOIL STREET, ROYAPURAM, CHENNAI-600 013, Ph 2598 1323 2595 6660