



Jai Kamal Paints

MANUFACTURERS OF PAINTS & VARNISH

POLYURETHANE ZINC PHOSPHATE

PRIMER GREY / RED

DESCRIPTION	:	A two pack polyurethane primer gives excellent adhesion and offers efficient protection against chemicals. It exhibits excellent corrosion resistance properties. When exposed to critical areas of chemical and other corrosion prone industries.
APPLICATION	:	The polyurethane primer has a very good bonding with steel, concrete wood surfaces, pulp and paper mills. Refineries, petro chemical industries and efficient treatment plants.
TYPE	:	Two pack Polyurethane Catalyst
COMPOSITION	:	Catalyst / Epoxy Resin with Zinc Phosphate.
COLOUR	:	Grey / Red
MIXING RATIO	:	3 : 1 by volume
POT LIFT	:	4 to 6 hrs.
APPLICATION	:	Brush, Roller & Airless Spray
RECOMMENDED	:	30 to 35 Microns per coat
THEORETICAL COVERAGE	:	15 to 18 Sqmt./ Ltr.
DRYING TIME	:	Touch Dry : 50 minutes Surface Dry : 4 to 6 hrs. Hard Dry : by overnight
OVERCOATING INTERVAL	:	Minimum - overnight Maximum - 4 Days
FLASH POINT	:	Above 22 °C
THINNER RECOMMENDED	:	“Jaikamal” P.U Thinner.
FINISH	:	Uniform Matt
KEEPING PROPERTIES:	:	9 months in sealed container at normal room temperature.
PACKING	:	20 ltr., 4 ltr., 1 ltr.

(THE INFORMATION IN THIS LEAFLET IS GIVEN IN GOOD FAITH, BUT WITHOUT WARRANTY)

‘THE DECORATIVE PROTECTION THAT STANDS THE TEST OF TIME’

(Old No.70) New No 169 MS KOIL STREET, ROYAPURAM, CHENNAI-600 013, Ph 2598 1323 2595 6660